

Data Sheet

HiTherm 2025, 2% Acrylic

Product Description

Product Name : Acrylic Coated Fiberglass

Color(s) : Tan

Product Description : Fiberglass fabric designed for high temperature removable insulation jacketing & welding curtains.

Product Specification

Substrate Type	Fiberglass/Plain Weave Fabric		
Coating Medium	Acrylic		
Width	60	(inches)	Method
	(nominal)		
Weight	18 ± 5%	(ounces/ sq. yard)	ASTM-D-3776
Overall Thickness	0.03 ± 0.001	(inches)	ASTM-D-1777
Tensile Strength	Warp= 250 / Fill= 200	(pounds/sq. inch)	ASTM-D-5034
Flame Resistance	Char Length.	1" Max.	ASTM-D-6413
	Afterglow	1 Second Max	
	Flame Out	1 Second Max.	
Operating Temperature	1000°F		ASTM-D-6413
Temperature Resistance	Melting Points 1523°F		

The data in this Data Sheet relates only to the specific material designated herein. To the best of our knowledge, the information contained herein accurate & HiTemp Materials Corp. assumes no liability for its accuracy or completeness. Final determination of suitability of any material is the sole responsibility of the user. All materials ay present unknown hazards & should be used with caution.