

HiTemp Materials Corporation

22552 Cuttler Road, +1 (832) 543 5500 New Caney, Texas - 77054 www.hitempmaterials.com

**Data Sheet** 

## HiTherm FR 1" Hook

## **Fasteners Gray**

## **Product Description**

Color(s) : Gray : Standard Sew on Hook Fasteners. **Product Name** 

**Product Description**: Hook fastener with a FR coating that meet FAA & FMV specifications and conforms

to Mil-Spec AA-55126A.

## **Product Specification**

Construction	Woven		
Material 100%	Nylon		
Width	1	(inch)	Method
Weight	0.007	(oz/inch)	ASTM-D-3776
Thickness	0.077	(inch)	
<b>Engaged Thickness</b>	0.131	(inch)	
Melting Point	392°F		
Per Square Inch	306 Hooks		
Peel Strength	1.12	(lbf)	ASTM-D-5170
Shear Strength	22.70	(lbf)	ASTM-D-5169
Stitch Tear Strength	4.4	(lbs)	ASTM-D-2261
<b>Breaking Strength</b>	205	(lbf)	ASTM-D-5035
Durability	2000 peels – 30% Closure Strength Reduction		
	5000 peels – 35% Closure Strength Reduction		
	10,000 peels – 45% Closure Strength Reduction		
	20,000 peels – 50% Closure Strength Reduction		
Recommended Storage	65°F - 75°F (18°C - 24°C) with relative humidity of 40% - 60%		

Conditions

The data in this Data Sheet relates only to the specific material designated herein. To the best of our knowledge, the information contained herein accurate & HiTemp Materials Corp. assumes no liability for its accuracy or completeness. Final determination of suitability of any material is the sole responsibility of the user. All materials ay present unknown hazards & should be used with caution.